

CABLE LENGTH

ATX CABLE	1x 600mm (m)
EPS CABLE	1x 600mm, 1x 700mm (m)
PCIE CABLE	2x 600mm, 2x 700mm (m)
SATA CABLE	2x 500mm, 600mm, 700mm (m), 1x 500mm, 600mm, 700mm, 800mm (m)
FOUR-PIN PERIPHERAL CABLE	1x 500mm, 600mm, 700mm, 1x 500mm, 600mm (m)
AC POWER	1x 1500mm (m)
MODULAR CABLE TYPE	Semi

CONNECTOR QUANTITY

24 PIN ATX	1x
EPS (CPU)	2x 8pin (4+4)
PCIE	4x 8pin (6+2), 2x 6pin
SATA	10x
FOUR-PIN PERIPHERAL	5x
FLOPPY	1x

POWER SPECS

AC Input	115 - 240 VAC, 10A, 50 - 60 Hz				
Rail	+3.3V	+5V	+12V	+5Vsb	-12V
Max Output	24A	24A	70A	3.0A	0.5A
			840W		

	120W	840W	15W	6W
Total	850W @ +50C			

ADDITIONAL DETAILS

OPERATING TEMPERATURE	0° to 50° C
JAPANESE CAPACITORS	100%
ECO MODE	No
MTBF	100,000 Hours
NET WEIGHT	7 lbs
SIZE	85mm (H) x 150mm (W) x 180mm (L)
APPROVALS	TUV, CB, CE, FCC, RCM, cTUVus, BSMI, WEEE, RoHS Compliance with ErP Lot 6 2013 Requirement
FAN SIZE / BEARING	140mm Double Ball Bearing