Products

What's Hot

Commercial

Service

# B150I PRO GAMING/WIFI/AURA

 $\textbf{CPU} \\ \textbf{Intel} \\ \textbf{®} \\ \textbf{Socket 1151 for 6} \\ \textbf{^{th} Generation Core} \\ \textbf{^{IT}} \\ \textbf{^{IT}}$ 

i3/Pentium®/Celeron® Processors

Supports Intel® 14 nm CPU

Supports Intel® Turbo Boost Technology 2.0

- \* The Intel® Turbo Boost Technology 2.0 support depends on the CPU types.
- \* Refer to www.asus.com for CPU support list

## ChipsetIntel® B150

Memory4 x DIMM, Max. 64GB, DDR4 2133 MHz Non-ECC, Un-buffered Memory

**Dual Channel Memory Architecture** 

Supports Intel® Extreme Memory Profile (XMP)

- \* Hyper DIMM support is subject to the physical characteristics of individual CPUs
- \* Refer to www.asus.com for the Memory QVL (Qualified Vendors Lists).

Graphic Integrated Graphics Processor- Intel® HD Graphics support

Multi-VGA output support : HDMI/DVI-D ports

- Supports HDMI with max. resolution 4096 x 2160 @ 24 Hz
- Supports DVI-D with max. resolution 1920 x 1200 @ 60 Hz

Maximum shared memory of 1024 MB

Supports Intel® InTru $^{\rm IM}$  3D, Quick Sync Video, Clear Video HD Technology, Insider  $^{\rm IM}$ 

Expansion Slots1 x PCle 3.0/2.0 x16 (x16 mode)

# StorageIntel® B150 chipset:

1 x M.2 Socket 3, with M key, type 2242/2260/2280 storage devices support (both SATA & PCIE mode)\*
4 x SATA 6Gb/s port(s),

LAN Intel® 1219V, 1 x Gigabit LAN Controller(s), GameFirst technology Anti-surge LANGuard

#### Wireless Data NetworkWi-Fi 802.11 a/b/g/n/ac

Supports dual band frequency 2.4/5 GHz

### Bluetooth Bluetooth V4.1

AudioSupremeFX 8-Channel High Definition Audio CODEC

- Supports : Jack-detection, Multi-streaming, Front Panel MIC Jack-retasking
- High quality 112 dB SNR stereo playback output

#### Audio Feature :

- SupremeFX Shielding™ Technology
- Optical S/PDIF out port(s) at back panel
- Sonic Radar II

# USB PortsIntel® B150 chipset:

5 x USB 3.0/2.0 port(s) (3 at back panel, blue, 2 at mid-board)

## Intel® B150 chipset:

4 x USB 2.0/1.1 port(s) (2 at back panel, , 2 at mid-board)

# Special Features Gamer's Guardian:

- ESD Guards on LAN, Audio, KBMS and USB3.0/2.0 ports
- DRAM Overcurrent Protection
- Stainless Steel Back I/O
- Highly Durable Components
- DIGI+ VRM

#### **ASUS EPU:**

- EPU

#### **ASUS Exclusive Features**:

- Al Suite 3
- Ai Charger
- ASUS UEFI BIOS EZ Mode featuring friendly graphics user interface
- USB 3.0 Boost
- Disk Unlocker

#### **Remote Entertainment**

- Media Streamer
- HyStream

#### **ASUS Quiet Thermal Solution:**

- Stylish Fanless Design Heat-sink solution
- ASUS Fan Xpert 2+

#### **ASUS EZ DIY:**

- ASUS CrashFree BIOS 3
- ASUS EZ Flash 3
- ASUS UEFI BIOS EZ Mode
- Push Notice

#### ASUS Q-Design:

- ASUS Q-Shield
- ASUS Q-LED (CPU, DRAM, VGA, Boot Device LED)
- ASUS O-DIMM

#### **RAMC**ache

**AURA: RGB Lighting Control** 

# Operating System SupportWindows® 10,64bit

Windows® 8.1, 64bit

Windows® 7, 32bit/64bit

## Back I/O Ports1 x PS/2 keyboard/mouse combo port(s)

- 1 x DVI
- 1 x HDMI
- 1 x LAN (RJ45) port(s)
- 3 x USB 3.0 Type-A + Type-C
- 2 x USB 2.0
- 1 x Optical S/PDIF out
- 6 x Audio jack(s)

#### Internal I/O Ports1 x USB 3.0 connector(s) support(s) additional 2 USB

3.0 port(s) (19-pin)

- 1 x USB 2.0 connector(s) support(s) additional 2 USB 2.0 port(s)
- 1 x M.2 Socket 3 for M Key, type 2242/2260/2280 devices
- 1 x TPM header
- 4 x SATA 6Gb/s connector(s)
- 1 x CPU Fan connector(s) (1 x 4 -pin)
- 1 x Chassis Fan connector(s) (1 x 4 -pin)
- 1 x 24-pin EATX Power connector(s)
- 1 x 8-pin ATX 12V Power connector(s)
- 1 x Front panel audio connector(s) (AAFP) 1 x System panel(s) (Q-Connector)
- 1 x Clear CMOS jumper(s)
- 1 x Water Pump header (4-pin)
- 1 x 14-1 pin TPM connector

## Accessories User's manual

ASUS Q-Shield

M.2 2242 mounting kit

2 x SATA 6Gb/s cable(s)

1 x M.2 Screw Package

1 x pack of cable tie

1 x CPU installation tool

1 x Supporting DVD

1 x 12 in 1 Cable Label (s)

# BIOS 128 Mb Flash ROM, UEFI AMI BIOS, PnP, DMI 3.0, WfM 2.0, SM BIOS 3.0, ACPI 5.0, Multi-language BIOS, ASUS EZ Flash 3,

CrashFree BIOS 3, F6 Qfan Control, F3 My Favorites, F9 Quick Note, Last Modified Log, F12 PrintScreen function, and ASUS DRAM SPD (Serial

Presence Detect) memory information

ManageabilityWfM 2.0, DMI 3.0, WOL by PME, PXE

Support Disc <sup>Drivers</sup>
ASUS Utilities
ASUS EZ Update

Anti-virus software (OEM version)

Form FactorMini ITX Form Factor

10 inch x 10 inch ( 17 cm x 17 cm )

Note\*: For a 2242 storage device, use the bundled 2242 mounting kit.

Specifications and features vary by model, and all images are illustrative. Please refer specification pages for full details.

\*Precise specifications and features vary by model . Please refer to the specification page

The product (electrical, electronic equipment, Mercury-containing button cell battery) should not be placed in municipal waste. Check local regulations for disposal of electronic products.



Products certified by the Federal Communications Commission and Industry Canada will be distributed in the United States and Canada. Please visit the ASUS USA and ASUS Canada websites for All specifications are subject to change without notice. Please check with your supplier for exact offers. Products may not be available in all markets.

Specifications and features vary by model, and all images are illustrative. Please refer specification pages for full details.

PCB color and bundled software versions are subject to change without notice.

Brand and product names mentioned are trademarks of their respective companies.

Want More?	
Who We Are	
Need Help?	
Community	

# Global / English

 $\hbox{Terms of Use Notice} \qquad \hbox{Privacy Policy} \qquad \hbox{@ASUSTeK Computer Inc. All rights reserved}.$